

**WHITE MASTERBATCHES TECHNOFIN®**

| Mark      | Polymer base | TiO <sub>2</sub> , % | Filler | Tint | Bulk density, g/cm <sup>3</sup> | MFI,<br>g/10 min 190°C/2,16 kg | Application        |       |            |                 |               |          |                   |                  |                      |
|-----------|--------------|----------------------|--------|------|---------------------------------|--------------------------------|--------------------|-------|------------|-----------------|---------------|----------|-------------------|------------------|----------------------|
|           |              |                      |        |      |                                 |                                | Multilayered films | Films | Thin films | PE and PP pipes | Blow moulding | PP films | Injection molding | Extrusion sheets | Cable insulation PVC |
| CPG 00682 | LLDPE        | 70                   |        | M    | 1,2±0,1                         | 10-35                          | ●                  | ●     | ●          |                 |               | ○        |                   |                  |                      |
| CPG 009   | LLDPE        | 65                   | Δ      | M    | 1,2±0,1                         | 8-20                           | ○                  | ●     | ●          |                 | ○             | ○        | ●                 | ●                | ○                    |
| CPG 0086  | LLDPE        | 60                   | Δ      | B    | 1,2±0,1                         | 5-25                           |                    | ●     | ●          |                 | ○             | ○        | ●                 | ●                | ○                    |
| CPG 007   | LLDPE        | 50                   | Δ      | M    | 1,2±0,1                         | 8-20                           |                    | ●     | ○          | ●               | ○             | ○        | ●                 | ●                | ○                    |
| CPG 0051  | LLDPE / LDPE | 45                   | Δ      | M    | 1,2±0,1                         | 0,5-5,0                        |                    | ○     | ○          | ●               | ○             |          | ○                 | ●                |                      |
| CPG 0058  | LLDPE / LDPE | 45                   | Δ      | B    | 1,2±0,1                         | 0,5-5,0                        |                    | ○     | ○          | ●               | ○             |          | ○                 | ●                |                      |
| CPG 0041  | LLDPE / LDPE | 25                   | Δ      | M    | 1,2±0,1                         | 0,5-5,0                        |                    | ○     |            | ●               | ○             |          | ○                 | ●                |                      |

● – recommended

Δ – contains

M – natural white

○ – application possible after testing

B – bluish

Technocom LLC shall not be responsible for the use, accuracy and completeness of the information offered, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Technocom LLC does not take any responsibility or liability for any information offered herein. The responsibility regarding the observance of third-party rights in the course of a subsequent processing and marketing of our products lies with the buyer.

