

ADDITIVE MASTERBATCHES ADDITECH®

Mark	Name	Polymer base	Recommended dosage, %	Application				
				PE and PP films	Blow molding	PE and PP pipes	Extrusion sheets	Injection molding
ACT	Antistatic	LLDPE	0,5-2	●	○		○	●
CA	Slip	LLDPE	1-2	●				●
CAB	Slip+antiblock	LLDPE	1-2	●				●
PD	Processing	LLDPE	0,5-2	●		●	●	
CC	UV stabilizer	LLDPE	1-3	●	●	●	●	●
MB	Desiccant	LDPE	1-5	●	○	●	○	○
AB	Antiblock	LLDPE	1-2	●	○		●	
AO	Antioxidant	LLDPE	1-2	●	●	●	●	●
TK	Talc concentrates	LLDPE	5-10	●	○		●	●
RL	Release agent	LLDPE	1-2		●			●
FA	Foaming agent	LLDPE	1-2,5			●	●	○
DO	Scent absorber	LLDPE	0,5-1,5	●	○	●	●	●
WB	Elasticity modifier	CPE	1-5	●	●	●	●	●
OX	Oxi-biodegradable	LLDPE	0,5-2	●	○		○	○
LA	Laser marking	LLDPE	0,5-2		○	●	●	●
HM	Viscosity modifier	PP	1-2					●
PL	Optical brightener	LLDPE	0,5-2	●	○		○	
OPP	Nucleator	PP	1-3	●	○		○	●

- – recommended
- – application possible after testing

Technocom LLC shall not be responsible for the use, accuracy and completeness of the information offered, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Technocom LLC does not take any responsibility or liability for any information offered herein. The responsibility regarding the observance of third-party rights in the course of a subsequent processing and marketing of our products lies with the buyer.

